

Sensormatic® SlimPad™ Pro Ultra•Max® Label Deactivator



Description

The SlimPad Pro is a ScanMax™ distance deactivator that delivers fast, reliable deactivation at the point-of-sale.

The unit's narrow design and flexible mounting options make it a perfect fit for most checkstands. It can be mounted flush with the counter, under the counter, or on a cantilever bracket at the end of the counter.

The SlimPad Pro can deactivate labels up to 15 cm (6 in.) above the surface of the pad at a throughput speed of up to 200 cm/sec. (80 in./sec.).

Features

- **Efficient.** SlimPad Pro's narrow design allows mounting on either side of the scanner to maintain the proper flow of products, first over the scanner, then over the deactivator.
- **Performance.** SlimPad Pro's deactivation height allows deactivation of both source tagged and retailer tagged merchandise.
- **Integrated visual notification of deactivation.** A LED on the deactivator provides visual notification of label deactivation.

Specifications

Power Rating

100-120 / 200-240 Vac, 1A @ 50-60Hz

Power Consumption

Typical: 10W @ 120V; 15W @ 240V

Max: 50W @ 120V and 240V

Operating Frequency

58 kHz (±200 Hz)

Operating Temperature

0° to 40° C (32 - 104° F)

SlimPad Dimensions

LxWxD: 35.2 x 11.4 x 8.9 cm
(13.9 x 4.5 x 3.5 in.)

Weight: 2.95 kg (9.7 lbs.)

Controller Dimensions

HxWxD: 10.1 x 26.2 x 22 cm
(4.0 x 10.3 x 8.7 in.)

Weight: 2.5 kg (5.5 lbs.)

Controller Emissions

47 CFR, Part 15

ENS 300 330

EN 301489

EN61000-3-2

EN61000-3-3

Controller Safety

UL60950

CSA C22.2 No. 60 950

EN 60 950

tyco
Safety
Products

ELECTRONIC ARTICLE SURVEILLANCE



The SlimPad Pro fits next to the scanner to ensure ease of use.



The compact ScanMax Pro Controller features table-top, vertical, and under-the-counter mounting options.

Remote module




The remote module can be mounted almost anywhere on the checkstand for visual and audible notification of deactivation. The module features a key switch for turning the deactivator on or off.

The SlimPad Pro will deactivate Ultra•Strip® II and Ultra•Strip III labels. Place labels within 7.6 cm (3 in.) of the bar code for optimal deactivation performance and convenience.



Ultra•Strip III



Ultra•Strip II


ScanMax Pro Controller

The ScanMax Pro Controller provides the power and operating capabilities to the deactivator antenna. It is compatible with all ScanMax Pro deactivator antennas. Its features include:


- Deactivates up to two labels per second.
- Small size requires minimal space.
- Optional mounting bracket for under-the-counter or sidewall installation.
- Automatically detects antenna type and remote module.
- Simple button press to select deactivation mode and label type.
- Auto phasing capability.
- Separate communications ports for POS and service.

For further details on all ScanMax Pro products, refer to the ScanMax Pro Deactivator Systems Planning Guide 8200-0054-02.

Mounting brackets



Under-the-counter mounting brackets



End-of-the-counter cantilever bracket

Product Codes

- ZBSMP-SL System, including deactivator, controller, remote alarm module, power cord
- ZESMPRO Controller with cord
- ZBSMPRO Controller only
- ZBSMPSP Deactivator only
- ZPSTP-RA Remote Alarm Module
- ZPSL-B2 Under-the-counter mounting bracket
- ZPSL-B3 End-of-the-counter cantilever bracket

tyco
Safety
Products